



URSA GLASSWOOL P422

Espesor 25 mm

Resistencia térmica 0,65 m²·K/W

Declaración Ambiental de Producto

Parámetro Evaluado	Unidad	Fabricación de los materiales			Fin de vida		
		Produccion	Transporte	Instalacion	Transporte	Proceso	Vertedero
		A1 a A3	A4	A5	C2	C3	C4
Global Warming Potential	Kg CO ₂ equiv.	1,11E+00	3,61E-01	9,26E-02	2,82E-03	0,00E+00	1,05E-02
Stratospheric Ozone Layer Depletion Potential	Kg CFC11 equiv.	5,55E-08	6,91E-10	9,74E-11	5,40E-12	0,00E+00	9,02E-11
Acidification Potential	Kg SO ₂ equiv.	5,90E-03	2,36E-03	2,89E-05	1,75E-05	0,00E+00	4,49E-05
Eutrophication Potential	Kg PO ₄ ³⁻ equiv.	6,69E-04	3,75E-04	1,74E-04	2,76E-06	0,00E+00	5,92E-06
Abiotic Resource Depletion Potential	Kg Sb equiv.	8,87E-03	2,43E-03	2,66E-05	1,90E-05	0,00E+00	4,02E-05
Photochemical Ozone Formation Potential	Kg ethane equiv.	4,26E-04	2,13E-04	2,78E-05	1,48E-06	0,00E+00	7,13E-06
Consumption of renewable primary energy	MJ (lower heating value)	3,05E+00	9,42E-03	2,83E-03	7,36E-05	0,00E+00	5,85E-03
Consumption of non-renewable primary energy	MJ (lower heating value)	2,10E+01	5,08E+00	5,89E-02	3,97E-02	0,00E+00	8,69E-02
Use of non-renewable secondary fuels	MJ (lower heating value)	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Use of renewable secondary fuels	MJ (lower heating value)	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Fresh water consumption	m ³	4,39E-01	1,49E-04	5,00E-05	1,17E-06	0,00E+00	1,44E-04
Waste production:	Kg	1,34E+00	1,64E-02	1,34E-01	1,28E-04	0,00E+00	5,53E-01
· hazardous	Kg	6,09E-03	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
· non hazardous	Kg	1,33E+00	1,64E-02	1,34E-01	1,28E-04	0,00E+00	5,53E-01
· radioactive	Kg	7,47E-04	9,18E-06	1,71E-08	7,18E-08	0,00E+00	0,00E+00
Output materials for	Kg	6,76E-02	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
· Reusing	Kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
· Recycling	Kg	6,76E-02	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
· Energy Recovery	Kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00